

Shaping Knowledge and Interoperable Graphs

Presenter: **Jose Emilio Labra Gayo**
WESO Research group
University of Oviedo, Spain



About me...

Main researcher at WESO (Web Semantics Oviedo)

Some books:

"*Web semántica*" (in Spanish), 2012

"*Validating RDF data*", 2017

"*Knowledge Graphs*", 2021

...and some software:

RDFShape (RDF playground)


rudof



<http://labra.weso.es>




2012



2017 HTML version:


<http://book.validatingrdf.com>




2021, HTML version

<https://kgbook.org/>

About Oviedo, Asturias



Princess of Asturias Awards



2002, Tim Berners-Lee in Asturias receiving the Prince of Asturias Award
Together with: Vinton Cerf, Lawrance Roberts and Robert Kahn




Tutorial materials

Interactive – through the web

RDFShape: RDF playground

Wikishape: Tailored to Wikibase



RDFShape

RDFShape is a playground for RDF data conversion, validation and visualization, among other features.

It supports the following tasks:

- RDF conversion between different formats like [Turtle](#) and [JSON-LD](#)
- RDF validation using [ShEx](#) (Shape Expressions) and [SHACL](#) (Shapes Constraint Language)
- RDF querying with [SPARQL](#)
- [RDFS](#) and [OWL](#) inference

You may jump straight in or check the examples in the navbar yourself :)



Command line

Rudof

Binaries in Windows, Linux, Mac

Interactive (Jupyter)

rudof

Python bindings



<https://rudof-project.github.io/tutorials>

Contents



Introduction to Knowledge graphs

Types of Knowledge Graphs:

RDF, Property graphs, Wikibase, RDF-Star

Shaping RDF: ShEx & SHACL, DCTAP

Shaping other types of Knowledge graphs:


Wikibase and Wikidata graphs

Property Graphs

RDF-1.2


Knowledge Graphs

Current notion of Knowledge Graphs, popular after Google, 2012*



Link: <https://www.blog.google/products/search/introducing-knowledge-graph-things-not/>



Knowledge Graphs



Knowledge Graphs

Knowledge graph = *a **graph of data***

*intended to accumulate and convey **knowledge** of the real world
whose **nodes** represent **entities** of interest and
whose **edges** represent **relations** between these entities.*



<https://kgbook.org/>

Applications of Knowledge Graphs

Improve search results

Question answering

Data governance


Handling heterogeneous data

Recommender systems

Chatbots, NLP, LLMs

Explainability in AI

...



Contents

Introduction to Knowledge graphs

 Types of Knowledge Graphs:

RDF, Property graphs, Wikibase, RDF-Star

Shaping RDF: ShEx & SHACL, DCTAP

Shaping other types of Knowledge graphs:

Wikibase and Wikidata graphs

Property Graphs

RDF-1.2

Types of Knowledge Graphs

- Traditional RDF
- Labeled Property graphs
- Wikibase graphs
- RDF 1.2

RDF

Resource Description Framework

Lingua franca of the Semantic Web

1997 1st public Working draft <https://www.w3.org/TR/WD-rdf-syntax-971002/>, RDF/XML

1999 1st W3C Rec <https://www.w3.org/TR/1999/REC-rdf-syntax-19990222/>, RDF Model and Syntax

2004 - RDF Revised <https://www.w3.org/TR/2004/REC-rdf-concepts-20040210/>, Turtle

2008 - SPARQL 1.0, <https://www.w3.org/TR/2008/REC-rdf-sparql-query-20080115/>

2014 - RDF 1.1 <https://www.w3.org/TR/rdf11-concepts/>, SPARQL 1.1, JSON-LD

2017 - SHACL 1.0 <https://www.w3.org/TR/2017/REC-shacl-20170720/>

2025 - RDF 1.2 <https://www.w3.org/TR/rdf12-concepts> Statements about triples



RDF graphs


Based on triples

(subject, predicate, object)

Most nodes are URIs

Interoperability

Simple & flexible





RDF ecosystem

One data model, several syntaxes: Turtle, N-Triples, JSON-LD

Vocabularies: RDF Schema, OWL, SKOS, etc.


Turtle

```
prefix :      <http://example.org/>
prefix rdfs:  <http://www.w3.org/2000/01/rdf-schema#>
prefix xsd:   <http://www.w3.org/2001/XMLSchema#>
prefix rdf:   <http://www.w3.org/1999/02/22-rdf-syntax-ns#>
```

```
:timbl rdfs:type      :Human ;
       :birthPlace   :london ;
       :name         "Tim Berners-Lee" ;
       :birthDate    "1955-06-08"^^xsd:date ;
       :employer     :CERN ;
       :knows        _:1 .

:london rdfs:type     :City, :Metropolis ;
       :country      :UK .

:CERN   rdfs:type     :Organization .
_:1     :birthPlace   :Spain .
```



<https://rdfshape.weso.es/link/17344285150>




RDF ecosystem: SPARQL

SPARQL = RDF query language and protocol

Enables the creation of SPARQL endpoints

```
SELECT ?person ?date ?country WHERE {  
  ?person :birthDate ?date .  
  ?person :birthPlace ?place .  
  ?place :country ?country  
}
```

?person	?date	?country
:timbl	1955-06-08	:UK




Let's check some RDF tools

Let's check the tools for RDF

- Declare that:
 - Tim Berner's Lee won the Princess of Asturias Award

- ☐ Did you use RDFShape?
- ☐ Did you use the Jupyter Colab?
- ☐ Did you use rudof as a CLI
- ☐ Do you think your RDF is OK?



Labeled Property graphs

Since ~2007, very popular model in industry

Neo4j, Amazon Neptune, Oracle, etc

Several query languages: Cypher, Gremlin, PGQL, ...

2024 - GQL has been published

Recent publication of ISO/IEC FDIS 39075

Developed by the “SQL” committee

Influenced by Cypher, PGQL, etc.


Property graphs

Graph structure with nodes and relationships (edges)

Nodes and edges can have:

- Labels
- A set of property-value pairs

Edges can be directed/undirected



Wikidata based Knowledge Graphs


Wikidata was created in 2012 as a collaborative knowledge graph

<https://www.wikidata.org/>

Developed and supported by Wikimedia Deutschland

Initial goal:

Support multilingual infoboxes in Wikipedia



Wikidata

English Wikipedia page of Tim Berners-Lee

WIKIPEDIA The Free Encyclopedia

Article Talk Read View source View history Search Wikipedia

Tim Berners-Lee

From Wikipedia, the free encyclopedia

Sir Timothy John Berners-Lee, OM, KBE, FRS, FREng, FRSA, DFBCS, RDI (born 8 June 1955),^[1] also known as **TimBL**, is an English computer scientist best known as the inventor of the World Wide Web. He is a Professorial Fellow of Computer Science at the University of Oxford^[2] and a professor at the Massachusetts Institute of Technology (MIT).^{[3][4]} Berners-Lee proposed an information management system on 12 March 1989,^{[5][6]} then implemented the first successful communication between a Hypertext Transfer Protocol (HTTP) client and server via the Internet in mid-November.^{[7][8][9][10][11]}

Berners-Lee is the director of the World Wide Web Consortium (W3C), which oversees the continued development of the Web. He co-founded (with his then wife-to-be Rosemary Leith) the World Wide Web Foundation. He is a senior researcher and holder of the 3Com founder's chair at the MIT Computer Science and Artificial Intelligence Laboratory (CSAIL).^[12] He is a director of the Web Science Research Initiative.

member of the at social

ment. He as Foreign

f the 100 as the tage NeXT received the ing the We

विकिपीडिया
एगो मुक्त ज्ञानकोष

खाला बनाई ...

टिम बर्नर्स-ली

पन्ना बातचीत पढ़ी संपादन करी इतिहास देखी

विकिपीडिया से

सर टिमोथी जॉन बर्नर्स-ली एगो अंगरेज इंजीनियर आ बैज्ञानिक हवें। इनके परसिद्धि वल्ल वाइड वेब के बनावेवाला के रूप में बा आ आजकालह ई ऑक्सफोर्ड यूनिवर्सिटी आ मैसाचुसेट्स यूनिवर्सिटी में प्रोफेसर बाड़ें।

Sir Tim Berners-Lee
OM KBE FRS FREng FRSA FBSC



Berners-Lee in 2014

जनम Timothy John Berners-Lee
8 जून 1955 (उमिर 67)
लंदन, इंग्लैंड, यूनाइटेड किंगडम

दूसरा नाँव TimBL
TBL

शिक्षा Emanuel Schoo

Bihari Wikipedia of Tim Berners-Lee

<http://www.wikidata.org/entity/Q80>

WIKIDATA

Main page
Community portal
Project chat
Create a new item
Recent changes
Random item
Query Service
Nearby
Help
Donate

Lexicographical data
Create a new Lexeme
Recent changes
Random Lexeme

Tools
What links here
Related changes
Special pages
Permanent link
Page information
Concept URI
Cite this page

Tim Berners-Lee (Q80)

English computer scientist, inventor of the World Wide Web (born 1955)
TimBL | Sir Tim Berners-Lee | Timothy John Berners-Lee | TBL | T. Berners-Lee | T Berners-Lee | Tim Berners Lee | T.J. Berners-Lee | Sir Timothy John Berners-Lee


► In more languages

Statements

instance of human edit

► 1 reference + add value

image edit



Sir Tim Berners-Lee (cropped).jpg
570 × 713; 178 KB

point in time 2014

media legend Tim Berners-Lee in 2014. (English)
Tim Berners-Lee i 2014. (Norwegian Bokmål)
Tim Berners-Lee i 2014. (Norwegian Nynorsk)

► 0 references + add reference

+ add value

sex or gender male edit

► 2 references + add value

Wikidata

Wikidata as a commons Knowledge Graph

119,272,346 items, 2,423,893,283 edits (11/2024):

<https://www.wikidata.org/wiki/Wikidata:Statistics>

Free and open license: CC0

Multilingual

Collaborative (Humans and bots)


Public SPARQL endpoint

Software that supports Wikidata = Wikibase

Example from Wikidata

Information about Tim Berners Lee

<http://www.wikidata.org/entity/Q80>



Wikibase

Wikibase: Software suite that implements Wikidata
(<https://wikiba.se/>)

Set of extensions of Media Wiki

(<https://www.mediawiki.org/wiki/Wikibase>)

Implemented in PHP (backend) + Javascript (frontend)

Can be hosted locally through Docker

Also available Cloud service: Wikibase.cloud (<https://www.wikibase.cloud/>)

Wikibase instance: Application using Wikibase software

More info: Wikibase.world



Wikibase and RDF

Wikibase offers an RDF serialization of each entity

Several ways to get the RDF serialization*:

- SPARQL endpoint: Query service
- RDF Dumps
- Directly, for example: <https://www.wikidata.org/wiki/Special:EntityData/Q80.ttl>

RDF dump format defined in: [RDF Dump Format specification](#)

Several namespaces:

[wd](#): for items

[wdt](#): for properties

...

Custom reification model to serialize qualifiers and references

Serialization of complex datatypes requires several triples

*There can be small differences between the RDF serializations as described [here](#)


Wikibase and RDF (example)

Simplified RDF dump

```
wd:Q80 a wikibase:Item ;
  wdt:P31 wd:Q5 ;
  wdt:P19 wd:Q84 ;
  wdt:P569 "1955-06-08T00:00:00Z"^^xsd:dateTime ;
  wdt:P108 wd:Q42944 ;
  p:P108 s:Q80-fcba864c, :Q80-4fe7940f
#...
.

:Q80-4fe7940f a wikibase:Statement ;
  ps:P108 wd:Q42944 ;
  pq:P580 "1984-01-01T00:00:00Z"^^xsd:dateTime ;
  pq:P582 "1994-01-01T00:00:00Z"^^xsd:dateTime .


s:Q80-fcba864c a wikibase:Statement ;
  ps:P108 wd:Q42944 ;
  pq:P580 "1980-06-01T00:00:00Z"^^xsd:dateTime ;
  pq:P582 "1980-12-01T00:00:00Z"^^xsd:dateTime .
```



<i>timBl</i>	wd:Q80
<i>London</i>	wd:Q84
<i>Human</i>	wd:Q5
<i>CERN</i>	wd:Q42944
<i>birthDate</i>	wdt:P569
<i>instanceOf</i>	wdt:P31
<i>birthPlace</i>	wdt:P19
<i>employer</i>	wdt:P108
<i>start</i>	pq:P580
<i>end</i>	pq:P582

Wikibase and RDF

Query service available: SPARQL endpoint



```
select ?name ?date ?country where {  
  wd:Q80 wdt:P1559 ?name .  
  wd:Q80 wdt:P569 ?date .  
  wd:Q80 wdt:P19 ?place .  
  ?place wdt:P17 ?country  
}
```

?name	?date	?country
Tim Berners-lee	1955-06-08	:UK

Try it: <https://w.wiki/5yGu>

RDF 1.2 (previously RDF-Star)

Currently under discussion (<https://github.com/w3c/rdf-star-wg/wiki>)


Add statements about triples (called triple terms)

Reifiers

```
:timbl rdfs:label "Tim Berners Lee" ;
      :employer :CERN {
        :start "1984" ;
        :end   "1994" ;
      }
      {
        :start "1980" ;
        :end   "1980" ;
      } .
```



```
:timbl rdfs:label "Tim Berners Lee" ;
      :employer :CERN .
_:r rdf:reifies <<( :timbl :employer :CERN )>> .
_:r :start "1984" ;
   :end   "1994" .
_:s rdf:reifies <<( :timbl :employer :CERN )>> .
_:s :start "1980" ;
   :end   "1980" .
```



Note:

In this example, we are asserting that Tim's employer is CERN

RDF 1.2: Non-asserted triple terms

Triple terms can be reified without being asserted


We can say that Tim's employer is the CERN according to Wikidata

But we don't need to assert whether Tim's employer is the CERN or not

```
:timbl rdfs:label "Tim Berners Lee" .
<< :timbl :employer :CERN >>
  :accordingTo :Wikidata ;
  :start      "1984" ;
  :end        "1994" .
<< :timbl :employer :CERN >>
  :accordingTo :Wikidata ;
  :start      "1980" ;
  :end        "1980" .
```



```
:timbl rdfs:label "Tim Berners Lee" .
_:1 rdf:reifies <<( :timbl :employer :CERN )>> ;
  :accordingTo :Wikidata ;
  :start      "1984" ;
  :end        "1994" .
_:2 rdf:reifies <<( :timbl :employer :CERN )>> ;
  :accordingTo :Wikidata ;
  :start      "1980" ;
  :end        "1980" .
```




RDF 1.2

RDF 1.2 also supports Wikibase style models

```
:timbl rdfs:label "Tim Berners Lee" ;
      :employer :CERN { | :start      1984 ;
                          :end        1994 | }
                          { | :start      1980 ;
                          :end        1980 | } ;
      :award :PA { | :time      2002 ;
                   :togetherWith :vint | } .
:vint rdfs:label "Vinton Cerf" .
```

```
:timbl rdfs:label "Tim Berners Lee" ;
      :employer :CERN ; :award :PA.
_:r rdf:reifies <<(:timbl :employer :CERN )>> ;
   :start      "1984" ;
   :end        "1994" .
_:s rdf:reifies <<(:timbl :employer :CERN )>> ;
   :start      "1980" ;
   :end        "1980" .
_:t rdf:reifies <<(:timbl :award :PA )>> ;
   :time      "2002" ;
   :togetherWith :vint .
:vint rdfs:label "Vinton Cerf" .
```



RDF 1.2


And things that Wikibase can not support, like qualifying qualifiers...

```

:timbl a :Human ;
  rdfs:label "Tim Berners Lee" ;
  :employer :CERN { | :start "1984"          { | :accordingTo :wikidata { | :statedIn "2024-05-02"^^xsd:date | } | } ;
                  | :end  "1994"          { | :accordingTo :wikidata { | :statedIn "2024-05-02"^^xsd:date | } | } ;
                  | }
                  { | :start "1980"          { | :accordingTo :wikidata { | :statedIn "2024-05-01"^^xsd:date | } | } ;
                  | :end  "1980"          { | :accordingTo :wikidata { | :statedIn "2024-05-01"^^xsd:date | } | } ;
                  | }
  :award      :PA { | :year 2002          { | :accordingTo :wikidata { | :statedIn "2024-05-01"^^xsd:date | } | } ;
                  | :together_with :vint { | :accordingTo :wikidata { | :statedIn "2024-05-01"^^xsd:date | } | } ;
                  | }
.

```

Do you want to draw that graph?



SPARQL 1.2

Current draft: <https://www.w3.org/TR/sparql12-query/>


Thanks to Oxigraph, rudof supports RDF 1.2 and SPARQL 1.2

Example query:

```
PREFIX : <http://example.org/>

SELECT ?person ?employer ?start ?end WHERE {
  ?person a :Human ;
          :employer ?employer { | :start ?start ;
                                :end   ?end
                                | }
}
```

Run some SPARQL 1.2 queries with rudof




Contents

Introduction to Knowledge graphs

Types of Knowledge Graphs:

RDF, Property graphs, Wikibase, RDF-Star

 Shaping RDF: ShEx & SHACL, DCTAP

Shaping other types of Knowledge graphs:

Shaping Wikibase and Wikidata graphs

Shaping Property Graphs

Shaping RDF-1.2



RDF, the good parts...

RDF as an integration language

RDF as a *lingua franca* for semantic web and linked data

Basis for knowledge representation

RDF flexibility

Data can be adapted to multiple environments

Reusable data by default

RDF tools

RDF data stores & SPARQL

Several serializations: Turtle, JSON-LD, RDF/XML...

Can be embedded in HTML (Microdata/RDFa)





RDF, the other parts


Consuming & producing RDF

Describing and validating RDF content

SPARQL endpoints are not well documented

Typical documentation = set of SPARQL queries

Difficult to know where to start doing queries






Why describe & validate RDF?

For producers

- Developers can understand the contents they are going to produce
- They can ensure they produce the expected structure
- Advertise and document the structure
- Generate interfaces

For consumers

- Understand the contents
- Verify the structure before processing it
- Query generation & optimization



Running example: some errors

Well formed RDF can contain
some mistakes

Usually, RDF processors don't complain
RDF is very flexible

```
:timbl a          :Human          ;  
       :name      "Tim Berners-Lee" ;  
       :knows     :bob             .  
  
:alice a          :Human ;  
       :name      234             .  
  
:bob   a          :Human          ;  
       :name      "Bob", "Robert" ;  
       :knows     :CERN            .  
  
:carol a          :Human ;  
       :birthPlace :london .  
  
:CERN  a          :Organization ;  
       :name      "CERN"          .
```

In other technologies...

Technology	Schema
Relational Databases	DDL
XML	DTD, XML Schema, RelaxNG, Schematron
JSON	JSON Schema
RDF	?

Fill that gap



ShEx & SHACL

2013 RDF Validation Workshop

Conclusions of the workshop:

There is a need of a higher level, concise language for RDF Validation

ShEx initially proposed (v 1.0)

2014 W3c Data Shapes WG chartered

2017 SHACL accepted as W3C recommendation

2017 ShEx 2.0 released as W3C Community group draft

2019 ShEx adopted by Wikidata

2025 IEEE ShEx (*work in progress*)

2025 Data Shapes WG chartered again for SHACL 1.2 (*work in progress*)


Example of a shape

A shape describes

The form of a node (node constraint)

Incoming/outgoing arcs from a node

Possible values associated with those arcs



RDF Node

```
:timbl rdfs:label "Tim Berners-Lee" ;
      :birthPlace :london ;
      :birthDate "1955-06-08"^^xsd:date ;
      :employer :CERN .
```

ShEx

```
<Researcher> {
  :name      xsd:string      ;
  :birthPlace @<Place>       ? ;
  :birthDate xsd:date        ? ;
  :employer  @<Organization> * ;
}
```



Shape Expressions - ShEx

Goal: Concise and human-readable language

3 syntaxes:

ShExC: Compact syntax, similar to Turtle or SPARQL

ShExJ: JSON(-LD), for the spec

ShExR: RDF, based on JSON-LD

Note: Round tripping is possible, convert from one to the other

Semantics inspired by regular expressions

ShEx libraries and demos

Implementations & libraries:

[shex.js](#): Javascript

[Jena-ShEx](#): Java

[SHaclEX](#): Scala (Jena/RDF4j)

[PyShEx](#): Python

[shex-java](#): Java

[Ruby-ShEx](#): Ruby

[RDF-Elixir](#): Elixir

[rudof](#): Rust 

Online demos & playgrounds

[ShEx-simple](#)

[RDFShape](#)

[Wikishape](#)

[ShEx-Java](#)

[ShExValidata](#)

More info: <http://shex.io>

Simple example

Prefix
declarations
as in
Turtle/SPARQL

```
prefix :      <http://example.org/>
prefix xsd:    <http://www.w3.org/2001/XMLSchema#>
prefix schema: <http://schema.org/>

:Book IRI AND {
  schema:name   xsd:string   ;
  :related      @:Book      *
}
```

Nodes conforming to `:Book` must

- Be `IRI`s and
- Have property `schema:name` with a value of type `xsd:string` (exactly one)
- Have property `:related` with values conforming to `:Book` (zero or more)

RDF Validation using ShEx

RDF Data

Schema

```
:Book IRI AND {
  :name xsd:string ;
  :related @:Book *
}
```

Shape map

```
:a@:Book ✓
:b@:Book, ✓
:c@:Book, ✗
:d@:Book, ✗
:e@:Book, ✗
:f@:Book ✗
```

```
:a :name "Title A" ;
   :related :b .
:b :related :a ;
   :name "Title B" .
:c :name "Title C1", "Title C2" .
:d :name 234 .
:e :namme "Title E" .
:f :name "Title F" ;
   :related :a, _:1 .
_:1 :name "Unknown title" .
```


Try it ([RDFShape](#))

Try it ([Simple ShExDemo](#))

Validation process

Input: RDF data, ShEx schema, Shape map

Output: Result shape map



Node constraints

Constraints over a node (without considering its neighbourhood)

```

:Book {
  :name          xsd:string
  :datePublished xsd:date
  :numberOfPages MinInclusive 1
  :author        @:Person
  :genre         [ :Fiction :NonFiction ] ;
  :isbn          /isbn:[0-9X]{10}/
  :publisher     IRI
  :audio         .
  :maintainer    @:Person OR
                 @:Organization
}
:Person {}
:Organization {}

```

```

:item23
  :name          "Weaving the Web"
  :datePublished "2012-03-05"^^xsd:date
  :numberOfPages 272
  :author        :timbl
  :genre         :NonFiction
  :isbn          "isbn:006251587X"
  :publisher     <http://www.harpercollins.com/>
  :audio         <http://audio.com/item23>
  :maintainer    :alice

```

Try it:

(RDF) \

Cardinalities

Inspired by regular expressions: +, ?, *, {m,n}

By default {1,1}

```
:Book {  
  :name          xsd:string          ;  
  :numberOfPages xsd:integer  ?      ;  
  :author        @:Person    +      ;  
  :publisher     IRI         ?      ;  
  :maintainer    @:Person    {1,3}  ;  
  :related       @:Book      *      ;  
}  
:Person {}  
:Organization {}
```

```
:item23  
  :name          "Weaving the Web"    ;  
  :numberOfPages 272                  ;  
  :author        :timbl, :markFischetti ;  
  :maintainer     :alice, :bob         .
```


Recursive schemas

Support for recursive (cyclic) data models is part of the spec
Well formed semantics based on stratified negation

```

:Book    {  :title      xsd:string    ;
            :author     @:Person      * ;
            :related    @:Book        * }
:Person  {  :name       xsd:string    ? ;
            :birthDate  xsd:date      ? ;
            :birthPlace @:Place       ? ;
            :knows      @:Person      * ;
            :worksFor   @:Company     * }
:Place   {  :name       xsd:string    ;
            :country    @:Country     }
:Country {  :name       xsd:string    }
:Company {  :name       xsd:string    ;
            :employee   @:Person      }

```



Open/Closed content models

RDF semantics mostly presume open content models

Shape expressions are open by default

Enable extensibility

But...some use cases require closed content models

Added CLOSED keyword

```
:Book {  
  :name    xsd:string  ;  
}
```

```
:Book CLOSED {  
  :name    xsd:string  ;  
}
```



```
:a :name "Weaving the web" ;  
   :isbn "006251587X" .
```



Try it: [RDFShape](#)

Open/Closed properties

Property values are closed by default (closed properties)

```
:Book {
  :code /isbn:[0-9X]{10}/ ;
}
```



✓ :item23 :code "isbn:006251587X" .
✗ :item23 :code 23 .

Properties can be repeated

```
:Book {
  :code /isbn:[0-9X]{10}/ ;
  :code /isbn:[0-9]{13}/
}
```



✓ :item23 :code "isbn:006251587X" ,
:code "isbn:9780062515872" .

EXTRA declares properties as open

```
:Book EXTRA :code {
  :code /isbn:[0-9X]{10}/ ;
}
```



✓ :item23 :code "isbn:006251587X" ,
:code 23 .

Triple expressions

“Unordered” regular expressions: Regular bag expressions

```
:Person {
  ( :name      xsd:string |
    :firstName xsd:string + ;
    :lastName  xsd:string
  ) ;
  :birthDate  xsd:date    ?
}
```

```
(name |
  firstName + ;
  lastName
) ;
birthDate ?
```

```
(n | f + ; l ) ; b?
```

```
:alice → n
:bob   → f l
:carol → f l f
```

```
:dave → n f
```

```
:alice :name      "Alice Cooper"      ;
       :birthDate "2010-02-23"^^xsd:date .

:bob   :firstName "Robert"             ;
       :lastName  "Smith"              .

:carol :firstName "Carol"              ;
       :lastName  "King"               ;
       :firstName "Carole"             .
```

```
:dave :name      "Dave Navarro"      ;
       :firstName "Dave"              .
```

Try it: [RDFShape](#)

Logical operators

Shape Expressions can be combined with **AND**, **OR**, **NOT**

```
:Book {
  :name    xsd:string ;
  :author  @:Person OR @:Organization ;
}

:AudioBook @:Book AND {
  :name      MaxLength 20 ;
  :readBy    @:Person    ;
} AND NOT {
  :numberOfPages . +
}

:Person {}
:Organization {}
```

```
:item24 :name      "Weaving the Web" ;
        :author    :timbl             ;
        :readBy     :timbl            .
```

```
:item23 :name      "Weaving the Web" ;
        :author    :timbl             ;
        :numberOfPages 272            ;
        :readBy     :timbl            .
```

ShEx allows negation (**NOT**) combined with recursion (semantics based on stratified negation)

Try it: [RDFShape](#)

Importing schemas

`import` statement can be used to import schemas

<http://validatingrdf.com/tutorial/examples/book.shex>

```
:Book {
  :title    xsd:string    ;
}
:Person {
  :name     xsd:string ? ;
}
```

```
import <https://www.validatingrdf.com/examples/book.shex>
```

```
:AudioBook @:Book AND {
  :title      MaxLength 20 ;
  :readBy     @:Person    ;
}
```

```
:item24 :name      "Weaving the Web" ;
        :author    :timbl             ;
        :readBy     :timbl             .
```

Try it: [RDFShape](#)

Machine processable annotations

Annotations based on RDF

Lots of applications, e.g. generate forms from shapes

```
prefix schema: <http://schema.org/>
prefix : <http://example.org/>
prefix xsd: <http://www.w3.org/2001/XMLSchema#>
prefix ui: <http://www.w3.org/ns/ui#>

start = @:User

:User {
  schema:name      xsd:string           // ui:label "Name"      ;
  schema:birthDate xsd:dateTime         // ui:label "Birth date" ;
  schema:gender    [ schema:Male schema:Female ] // ui:label "Gender"
}
```

:User

Name:

Birth date:

Gender:

Try it:

[Eric's demo](#)

<https://rdfshape.weso.es/link/17095003321>

More complex Shape Maps

Shape Maps define which nodes validate with which shapes

Examples:

{ FOCUS <code>a</code> :Person } @:User	https://rdfshape.weso.es/link/17095033013
{ FOCUS <code>schema:name</code> _ } @:Book	https://rdfshape.weso.es/link/17095014386
SPARQL <code>"""</code> PREFIX <code>schema:</code> <http://schema.org/> SELECT ?book WHERE { ?book <code>schema:name</code> ?name; <code>schema:author</code> ?author } <code>"""</code> @:Book	https://rdfshape.weso.es/link/17095031848

Inheritance model for ShEx

extends allows to reuse existing shapes adding new content

Handles closed properties and shapes

```
:Book {
  :name      xsd:string ;
  :author    @:Person   ;
  :code      /isbn:[0-9]{13}/ ;
  :code      /isbn:[0-9X]{10}/
}

:LibraryBook extends @:Book {
  :code      /internal:[0-9]*/ ;
}
```

```
:item23 :name      "Weaving the Web" ;
        :author    :timbl             ;
        :code      "isbn:006251587X"   ;
        :code      "isbn:9780062515872" ;
        :code      "internal:234"     .
```

Other features

Multiple inheritance

Abstract shapes

More details: ***Shape Expressions with Inheritance***, Iovka Boneva, Jose Emilio Labra Gayo, Eric Prud'hommeaux, Katherine Thornton, Andra Waagmeester
Extended Semantic Web Conference, Portoroz, Slovenia, 2025 – 2025
https://labra.weso.es/publication/2025_shex_inheritance/

Try it:

<https://rdfshape.weso.es/link/17487753484>

3 syntaxes: ShExC, ShExJ, ShExR

ShExC

```
prefix :      <http://example.org/>
prefix xsd:   <http://www.w3.org/2001/XMLSchema#>
prefix schema: <http://schema.org/>

:Book {
  schema:name    xsd:string    ;
  :related       @:Book        *
}
```

ShExR (RDF, Turtle)

```
:Book a sx:ShapeDecl ;
sx:shapeExpr [ a sx:Shape ;
sx:expression [ a sx:EachOf ;
sx:expressions (
  [ a sx:TripleConstraint ;
sx:predicate schema:name ;
sx:valueExpr [ a sx:NodeConstraint ;
sx:datatype xsd:string
] ]
[ a sx:TripleConstraint ;
sx:predicate :related ;
sx:valueExpr [ a sx:NodeConstraint ;
sx:valueExpr :Book ] ] ) ] ] .
```

ShExJ (JSON LD)

```
{ "type" : "Schema",
  "@context" : "http://www.w3.org/ns/shex.jsonld",
  "shapes" : [ {
    "type" : "Shape",
    "id" : "http://example.org/Book",
    "expression" : {
      "type" : "EachOf",
      "expressions" : [ {
        "type" : "TripleConstraint",
        "predicate" : "http://schema.org/name",
        "valueExpr" : {
          "type" : "NodeConstraint",
          "datatype" : "http://www.w3.org/2001/XMLSchema#string"
        }
      },
      { "predicate" : "http://example.org/related",
        "valueExpr" : "http://example.org/Book",
        "min" : 0,
        "max" : -1,
        "type" : "TripleConstraint"
      }
    ]
  } ] }
```

It's possible to
roundtrip from
each one

SHACL

W3C recommendation: <https://www.w3.org/TR/shacl/> (July 2017)

Inspired by SPIN, OSLC & ShEx

2 parts: SHACL-Core, SHACL-SPARQL

Syntax = RDF vocabulary

ShEx and SHACL

ShEx

```
<Researcher> {  
  :name      xsd:string      ;  
  :birthPlace @:Place        ? ;  
  :birthDate xsd:date         ? ;  
  :employer  @:Organization * ;  
  :knows     @:Person        *  
}
```

SHACL

```
<Researcher> a sh:NodeShape ;  
  sh:targetClass :Human ;  
  sh:property [ sh:path rdfs:label ;  
                 sh:minCount 1; sh:maxCount 1;  
                 sh:datatype xsd:string ;  
               ] ;  
  sh:property [ sh:path :birthPlace ;  
                 sh:node <Place>  
               ] ;  
  sh:property [ sh:path :birthDate ;  
                 sh:maxCount 1;  
                 sh:datatype xsd:date  
               ] ;  
  sh:property [ sh:path :employer ;  
                 sh:node <Organization>  
               ] ;  
  sh:property [ sh:path :knows ;  
                 sh:node <Researcher>  
               ] .
```

Note:

Cyclic data models are implementation dependent in SHACL

Try it: <https://tinyurl.com/yh28fsct>

ShEx and SHACL

Comparing ShEx (compact syntax) with SHACL (compact syntax*)

ShEx

```
:Researcher {  
  :name      xsd:string      ;  
  :birthPlace @:Place        ? ;  
  :birthDate xsd:date        ? ;  
  :employer  @:Organization * ;  
  :knows     @:Researcher   *  
}
```

SHACL

```
shape @:Researcher -> :Human {  
  rdfs:label xsd:string [1..1] ;  
  :birthPlace @:Place        ;  
  :birthDate xsd:date        [1..] ;  
  :employer  @:Organization  ;  
  :knows     @:Researcher  
}
```

Note: SHACL Compact syntax is being discussed for SHACL 1.2
More info: <https://w3c.github.io/shacl/shacl-compact-syntax/>

Some SHACL implementations

Name	Parts	Language - Library	Comments
Topbraid SHACL API	SHACL Core, SPARQL	Java (Jena)	Used by TopBraid composer
SHACL playground	SHACL Core	Javascript (rdflib.js)	http://shacl.org/playground/
SHACL-S (SHacLEX)	SHACL Core	Scala (Jena, RDF4j)	http://rdfshape.weso.es
pySHACL	SHACL Core, SPARQL	Python (rdflib)	https://github.com/RDFLib/pySHACL
Corese SHACL	SHACL Core, SPARQL	Java (STTL)	http://wimmics.inria.fr/corese
RDFUnit	SHACL Core, SPARQL	Java (Jena)	https://github.com/AKSW/RDFUnit
Jena SHACL	SHACL Core, SPARQL	Java (Jena)	https://jena.apache.org/
RDF4j SHACL	SHACL Core	Java (RDF4J)	https://rdf4j.org
Stardog	SHACL Core, SPARQL	Java	https://www.stardog.com
Zazuko SHACL	SHACL Core	Javascript	https://github.com/zazuko/rdf-validate-shacl
maplib	SHACL Core	Rust	https://github.com/DataTreehouse/maplib
rudof 	SHACL core (in progress)	Rust	https://rudof-project.github.io/

RDFShape online demo supports: SHacLEX (SHACL-s), JenaSHACL, SHACL TQ (SHACL TopBraid API)

Basic example

```
prefix :      <http://example.org/>
prefix sh:    <http://www.w3.org/ns/shacl#>
prefix xsd:   <http://www.w3.org/2001/XMLSchema#>
prefix schema: <http://schema.org/>
```

```
:UserShape a sh:NodeShape ;
  sh:targetNode :alice, :bob, :carol ;
  sh:nodeKind sh:IRI ;
  sh:property :hasName,
              :hasEmail .
:hasName sh:path schema:name ;
  sh:minCount 1;
  sh:maxCount 1;
  sh:datatype xsd:string .
:hasEmail sh:path schema:email ;
  sh:minCount 1;
  sh:maxCount 1;
  sh:nodeKind sh:IRI .
```

Shapes graph

```
:alice schema:name "Alice Cooper" ;
       schema:email <mailto:alice@mail.org> .

:bob   schema:firstName "Bob" ;
       schema:email <mailto:bob@mail.org> . ☹️

:carol schema:name "Carol" ;
       schema:email "carol@mail.org" . ☹️
```

Data graph

Try it. RDFShape <https://tinyurl.com/y46b2f8q>

Same example with blank nodes

```
prefix :      <http://example.org/>
prefix sh:    <http://www.w3.org/ns/shacl#>
prefix xsd:   <http://www.w3.org/2001/XMLSchema#>
prefix schema: <http://schema.org/>
```

```
:UserShape a sh:NodeShape ;
  sh:targetNode :alice, :bob, :carol ;
  sh:nodeKind sh:IRI ;
  sh:property [
    sh:path      schema:name ;
    sh:minCount  1; sh:maxCount 1;
    sh:datatype  xsd:string ;
  ] ;
  sh:property [
    sh:path      schema:email ;
    sh:minCount  1; sh:maxCount 1;
    sh:nodeKind  sh:IRI ;
  ] .
```

```
:alice schema:name "Alice Cooper" ;
       schema:email <mailto:alice@mail.org> .

:bob   schema:firstName "Bob" ;
       schema:email <mailto:bob@mail.org> . ☹️

:carol schema:name "Carol" ;
       schema:email "carol@mail.org" . ☹️
```

Data graph

Shapes graph


Try it. RDFShape <https://tinyurl.com/y4ycv2vn>

Some definitions about SHACL

Shape: collection of targets and constraints components

Targets: specify which nodes in the data graph must conform to a shape

Constraint components: Determine how to validate a node



Shapes graph and data graph

Conceptually: 2 graphs

Shapes graph: an RDF graph that contains shapes

Data graph: an RDF graph that contains data to be validated

Note: They can be the same

```
:UserShape a sh:NodeShape ;  
  sh:targetNode :alice, :bob, :carol ;  
  sh:nodeKind sh:IRI ;  
  sh:property :hasName,  
              :hasEmail .  
:hasName sh:path schema:name ;  
  sh:minCount 1;  
  sh:maxCount 1;  
  sh:datatype xsd:string .  
. . .
```

Shapes graph

```
:alice schema:name "Alice Cooper" ;  
       schema:email <mailto:alice@mail.org> .  
  
:bob   schema:firstName "Bob" ;  
       schema:email <mailto:bob@mail.org> .  
  
:carol schema:name "Carol" ;  
       schema:email "carol@mail.org" .
```

Data graph

Validation Report

The output of the validation process is a list of violation errors

No errors $\Rightarrow$ RDF conforms to shapes graph

```
[ a          sh:ValidationReport ;  
  sh:conforms true  
].
```

```
[ a          sh:ValidationReport ;  
  sh:conforms false ;  
  sh:result  [  
    a          sh:ValidationResult ;  
    sh:focusNode :bob ;  
    sh:message  
      "MinCount violation. Expected 1, obtained: 0" ;  
    sh:resultPath schema:name ;  
    sh:resultSeverity sh:Violation ;  
    sh:sourceConstraintComponent  
      sh:MinCountConstraintComponent ;  
    sh:sourceShape :hasName  
  ] ;  
  ...
```



SHACL processor

Shapes graph
with target
declarations

```
:UserShape a sh:NodeShape ;  
  sh:targetNode :alice, :bob, :carol ;  
  sh:nodeKind sh:IRI ;  
  sh:property :hasName,  
              :hasEmail .  
:hasName sh:path schema:name ;  
  sh:minCount 1;  
  sh:maxCount 1;  
  sh:datatype xsd:string .  
. . .
```

Data
Graph

```
:alice schema:name "Alice Cooper" ;  
       schema:email <mailto:alice@mail.org> .  
  
:bob   schema:name "Bob" ;  
       schema:email <mailto:bob@mail.org> .  
  
:carol schema:name "Carol" ;  
       schema:email <mailto:carol@mail.org> .  
.
```



SHACL
Processor



Validation report

```
[ a sh:ValidationReport ;  
  sh:conforms true  
].
```


Importing shapes graphs

SHACL processors follow `owl:imports` declarations

It extends the current shapes graph with the imported shapes

```
:UserShape a sh:NodeShape ;  
  sh:targetNode :alice, :bob, :carol ;  
  sh:nodeKind sh:IRI ;  
  sh:property :hasName .  
:hasName sh:path schema:name ;  
  sh:minCount 1;  
  sh:maxCount 1;  
  sh:datatype xsd:string .
```



```
<> owl:imports <http://example.org/UserShapes> .  
  
:TeacherShape a sh:NodeShape;  
  sh:targetClass :Teacher ;  
  sh:node :UserShape ;  
  sh:property [  
    sh:path :teaches ;  
    sh:minCount 1;  
    sh:datatype xsd:string;  
  ] .
```

Node and property shapes

2 types of shapes:

NodeShape: constraints about shapes of nodes

PropertyShapes: constraints on property path values of a node



Node Shapes

Constraints about a focus node

```
:UserShape a sh:NodeShape ;  
    sh:nodeKind      sh:IRI ;  
    sh:targetClass   :User .
```

```
:alice a :User .  
  
<http://example.org/bob> a :User .  
  
_:1 a :User .
```



Try it: <https://tinyurl.com/y6qyqo5g>

Property shapes

Constraints about a given property and its values for the focus node

`sh:property` associates a shape with a property shape

`sh:path` identifies the path

```
:User a sh:NodeShape ;  
  sh:property [  
    sh:path      schema:email ;  
    sh:nodeKind  sh:IRI  
  ] .
```

```
:alice a :User ;  
       schema:email <mailto:alice@mail.org> .  
  
:bob   a :User;  
       schema:email <mailto:bob@mail.org> . ☹️  
  
:carol a :User;  
       schema:email "carol@mail.org" . ☹️
```

Paths in property shapes

Subset of SPARQL property paths using the following names:

inversePath

alternativePath

zeroOrMorePath

oneOrMorePath

zeroOrOnePath

```
:User a sh:NodeShape, rdfs:Class ;  
  sh:property [  
    sh:path [sh:inversePath schema:follows ];  
    sh:nodeKind sh:IRI ;  
  ] .
```

```
:alice a :User;  
       schema:follows :bob .  
  
:bob   a :User .  
  
:carol a :User;  
       schema:follows :alice .  
  
_:1 schema:follows :bob .
```



Constraint components

Constraints associated with shapes

They have parameters whose values specify the constraints

SHACL-core provides a list of predefined constraint components

Most of them have one parameter which identifies them

Convention:

Parameter: `sh:xx`

Constraint component: `sh:xxConstraintComponent`

```
:UserShape a          sh:NodeShape ;  
           sh:nodeKind sh:IRI .
```

Constraint component
`sh:nodeKindConstraintComponent`

Parameter
`sh:nodeKind`

Value of Parameter
`sh:IRI ;`

NOTE: Custom constraint components
can be defined in SHACL-SPARQL

Repeated parameter

Each value of the parameter declares a different constraint

```
:UserShape a sh:NodeShape;  
sh:class foaf:Person ;  
sh:class schema:Person .
```

```
:alice a schema:Person, foaf:Person .  
:bob a schema:Person .
```



SHACL Core constraint components

Type	Constraints
Cardinality	minCount, maxCount
Types of values	class, datatype, nodeKind
Values	node, in, hasValue, property
Range of values	minInclusive, maxInclusive minExclusive, maxExclusive
String based	minLength, maxLength, pattern
Language based	languageIn, uniqueLang
Logical constraints	not, and, or, xone
Closed shapes	closed, ignoredProperties
Property pair constraints	equals, disjoint, lessThan, lessThanOrEquals
Non-validating constraints	name, description, order, group
Qualified shapes	qualifiedValueShape, qualifiedValueShapesDisjoint qualifiedMinCount, qualifiedMaxCount

See later



Human friendly messages

Message declares the message that will appear in the validation report in case of violation

```
:UserShape a sh:NodeShape ;  
  sh:targetClass :User ;  
  sh:property [  
    sh:path      schema:name ;  
    sh:minCount  1 ;  
    sh:message   "Where is the name?"  
  ] .
```



```
:bob a :User ;  
  schema:alias "Bob" . ☹️
```



```
:report a :ValidationReport ;  
sh:conforms false ;  
sh:result [ a sh:ValidationResult ;  
  sh:resultSeverity      sh:Violation ;  
  sh:sourceConstraintComponent sh:MinCountConstraintComponent ;  
  sh:sourceShape         ... ;  
  sh:focusNode           :bob ;  
  sh:resultPath          schema:name ;  
  sh:resultMessage       "Where is the name?" ;  
] .
```

Severities

Declare the level of the violation

3 predefined levels: Violation (default), Warning, Info

```
:UserShape a sh:NodeShape ;  
sh:targetClass :User ;  
sh:property [  
  sh:path      schema:name ;  
  sh:datatype  xsd:string ;  
  sh:severity  sh:Warning  
] .
```



```
:bob a :User ;  
schema:alias "Bob" .
```



```
:report a :ValidationReport ;  
sh:conforms false ;  
sh:result [ a sh:ValidationResult ;  
  sh:resultSeverity      sh:Warning ;  
  sh:sourceConstraintComponent sh:MinCountConstraintComponent ;  
  sh:sourceShape          ... ;  
  sh:focusNode             :bob ;  
  sh:resultPath            schema:name ;  
  sh:resultMessage         "MinCount Error" ;  
] .
```

Deactivating shapes

Deactivate a shape

Useful when importing shapes

UserShapes

```
:UserShape a sh:NodeShape;  
  sh:targetClass :User ;  
  sh:property :HasName ;  
  sh:property :HasEmail .  
  
:HasName sh:path schema:name ;  
  sh:datatype xsd:string .  
  
:HasEmail sh:path schema:email ;  
  sh:minCount 1;  
  sh:nodeKind sh:IRI .
```

```
<> owl:imports <UserShapes> .  
  
:TeacherShape a sh:NodeShape;  
  sh:targetClass :Teacher ;  
  sh:node :UserShape ;  
  sh:property [ sh:path :teaches ;  
    sh:minCount 1;  
    sh:datatype xsd:string;  
  ] .  
  
:HasEmail sh:deactivated true .
```

Target declarations

Targets specify nodes that must be validated against the shape


Several types

Value	Description
targetNode	Directly point to a node
targetClass	All nodes that have a given type
targetSubjectsOf	All nodes that are subjects of some predicate
targetObjectsOf	All nodes that are objects of some predicate

Target node

Directly declare which nodes must validate the against the shape

```
:UserShape a sh:NodeShape ;  
  sh:targetNode :alice, :bob, :carol ;  
  sh:property [  
    sh:path schema:name ;  
    sh:minCount 1;  
    sh:maxCount 1;  
    sh:datatype xsd:string ;  
  ] ;  
  sh:property [  
    sh:path schema:email ;  
    sh:minCount 1;  
    sh:maxCount 1;  
    sh:nodeKind sh:IRI ;  
  ] .
```



```
:alice schema:name "Alice Cooper" ;  
      schema:email <mailto:alice@mail.org> .  
  
:bob   schema:givenName "Bob" ;  
      schema:email <mailto:bob@mail.org> .  
  
:carol schema:name "Carol" ;  
      schema:email "carol@mail.org" .
```

Target class

Selects all nodes that have a given class

Looks for `rdf:type` declarations*

```
:UserShape a sh:NodeShape ;  
  sh:targetClass :User ;  
  sh:property [  
    sh:path schema:name ;  
    sh:minCount 1;  
    sh:maxCount 1;  
    sh:datatype xsd:string ;  
  ] ;  
  sh:property [  
    sh:path schema:email ;  
    sh:minCount 1;  
    sh:maxCount 1;  
    sh:nodeKind sh:IRI ;  
  ] .
```

```
:alice a :User;  
      schema:name "Alice Cooper" ;  
      schema:email <mailto:alice@mail.org> .  
  
:bob a :User;  
     schema:givenName "Bob" ;  
     schema:email <mailto:bob@mail.org> .  
  
:carol a :User;  
       schema:name "Carol" ;  
       schema:email "carol@mail.org" .
```

* Also looks for `rdfs:subClassOf`*/`rdf:type` declarations

Implicit class target

A shape with type `sh:Shape` and `rdfs:Class` is a scope class of itself
The `targetClass` declaration is implicit

```
:User a sh:NodeShape, rdfs:Class ;  
  sh:property [  
    sh:path schema:name ;  
    sh:minCount 1;  
    sh:maxCount 1;  
    sh:datatype xsd:string ;  
  ] ;  
  sh:property [  
    sh:path schema:email ;  
    sh:minCount 1;  
    sh:maxCount 1;  
    sh:nodeKind sh:IRI ;  
  ] .
```

```
:alice a :User;  
  schema:name "Alice Cooper" ;  
  schema:email <mailto:alice@mail.org> .  
  
:bob a :User;  
  schema:givenName "Bob" ;  
  schema:email <mailto:bob@mail.org> .  
  
:carol a :User;  
  schema:name "Carol" ;  
  schema:email "carol@mail.org" .
```

targetSubjectsOf

```
:UserShape a sh:NodeShape;  
sh:targetSubjectsOf :teaches ;  
sh:property [  
  sh:path schema:name ;  
  sh:minCount 1;  
  sh:maxCount 1;  
  sh:datatype xsd:string ;  
] .
```

```
:alice :teaches :Algebra ;      #Passes as :UserShape  
      schema:name "Alice" .  
  
:bob   :teaches :Logic ;        #Fails as :UserShape  
      foaf:name "Robert" .  
  
:carol foaf:name 23 .           # Ignored
```


targetObjectsOf

```
:UserShape a          sh:NodeShape;  
sh:targetObjectsOf :isTaughtBy ;  
sh:property [  
  sh:path          schema:name ;  
  sh:minCount 1;  
  sh:maxCount 1;  
  sh:datatype xsd:string ;  
] .
```

```
:alice schema:name "Alice" . #Passes as :UserShape  
:bob    foaf:name "Robert" . #Fails as :UserShape  
:carol  foaf:name 23 .        # Ignored  
:algebra :isTaughtBy :alice, :bob .
```

Core constraint components

Type	Constraints
Cardinality	minCount, maxCount
Types of values	datatype, class, nodeKind
Values	node, in, hasValue
Range of values	minInclusive, maxInclusive minExclusive, maxExclusive
String based	minLength, maxLength, pattern, stem, uniqueLang
Logical constraints	not, and, or, xone
Closed shapes	closed, ignoredProperties
Property pair constraints	equals, disjoint, lessThan, lessThanOrEquals
Non-validating constraints	name, value, defaultValue
Qualified shapes	qualifiedValueShape, qualifiedMinCount, qualifiedMaxCount

Cardinality constraints

Constraint	Description
minCount	Restricts minimum number of triples involving the focus node and a given predicate. Default value: 0
maxCount	Restricts maximum number of triples involving the focus node and a given predicate. If not defined = unbounded

```
:User a sh:NodeShape ;  
  sh:property [  
    sh:path      schema:follows ;  
    sh:minCount  2 ;  
    sh:maxCount  3 ;  
  ] .
```

```
:alice schema:follows :bob,  
                                     :carol .  
  
:bob   schema:follows :alice . ☹️  
  
:carol schema:follows :alice,  
                                     :bob,  
                                     :carol, ☹️  
                                     :dave .
```

Datatypes of values

Constraint	Description
datatype	Restrict the datatype of all value nodes to a given value

```
:User a sh:NodeShape ;  
  sh:property [  
    sh:path      schema:birthDate ;  
    sh:datatype  xsd:date ;  
  ] .
```

```
:alice schema:birthDate "1985-08-20"^^xsd:date .  
:bob   schema:birthDate "Unknown"^^xsd:date .  
:carol schema:birthDate 1990 .
```



Class of values

Constraint	Description
class	Verify that each node in an instance of some class It also allows instances of subclasses*

(*) The notion of SHACL instance is different from RDFS
It is defined as `rdfs:subClassOf*/rdf:type`

```
:User a sh:NodeShape, rdfs:Class ;  
  sh:property [  
    sh:path schema:follows ;  
    sh:class :User  
  ] .
```

```
:Manager rdfs:subClassOf :User .  
  
:alice a :User;  
       schema:follows :bob .  
:bob   a :Manager ;  
       schema:follows :alice .  
:carol a :User;  
       schema:follows :alice, :dave .  
:dave  a :Employee .
```



Kind of values

Constraint	Description
nodeKind	Possible values: BlankNode, IRI, Literal, BlankNodeOrIRI, BlankNodeOrLiteral, IRIOrLiteral

```
:User a sh:NodeShape, rdfs:Class ;  
  sh:property [  
    sh:path      schema:name ;  
    sh:nodeKind  sh:Literal ;  
  ] ;  
  sh:property [  
    sh:path      schema:follows ;  
    sh:nodeKind  sh:BlankNodeOrIRI ;  
  ] ;  
  sh:nodeKind  sh:IRI .
```

```
:alice a :User ;  
  schema:name      _:1 ;  
  schema:follows   :bob .  
  
:bob a :User ;  
  schema:name      "Robert" ;  
  schema:follows   [ schema:name "Dave" ] .  
  
:carol a :User ;  
  schema:name      "Carol" ;  
  schema:follows   "Dave" .  
  
_:1 a :User .
```



Constraints on values

Constraint	Description
hasValue	Verifies that the focus node has a given value
in	Enumerates the value nodes that a property may have

```
:User a sh:NodeShape, rdfs:Class ;  
  sh:property [  
    sh:path      schema:affiliation ;  
    sh:hasValue  :OurCompany ;  
  ] ;  
  sh:property [  
    sh:path schema:gender ;  
    sh:in   (schema:Male schema:Female)  
  ] .
```

```
:alice a :User;  
       schema:affiliation :OurCompany ;  
       schema:gender schema:Female .  
  
:bob   a :User;  
       schema:affiliation :AnotherCompany ;  
       schema:gender schema:Male .  
  
:carol a :User;  
       schema:affiliation :OurCompany ;  
       schema:gender schema:Unknown .
```



Constraints on values with another shape

Constraint	Description
node	All values of a given property must have a given shape Recursion is not allowed in current SHACL

```
:User a sh:NodeShape, rdfs:Class ;  
  sh:property [  
    sh:path schema:worksFor ;  
    sh:node :Company ;  
  ] .
```

```
:Company a sh:Shape ;  
  sh:property [  
    sh:path schema:name ;  
    sh:datatype xsd:string ;  
  ] .
```

```
:alice a :User;  
       schema:worksFor :OurCompany .
```

```
:bob   a :User;  
       schema:worksFor :Another .
```



```
:OurCompany  
  schema:name "OurCompany" .
```


```
:Another  
  schema:name 23 .
```


Value shapes and recursion

Can we define cyclic data models as the following?

```
:User a sh:NodeShape ;
  sh:property [
    sh:path schema:worksFor ;
    sh:node :Company ;
  ] .

:Company a sh:Shape ;
  sh:property [
    sh:path schema:name ;
    sh:datatype xsd:string ;
  ] ;
  sh:property [
    sh:path schema:employee ;
    sh:node :User ;
  ] .
```



```
:alice schema:worksFor :OneCompany .
:bob schema:worksFor :OneCompany .
:carol schema:worksFor :OneCompany .

:OneCompany schema:name "One" ;
  schema:employee :alice, :bob, :carol .
```

SHACL spec leaves this as implementation dependent


Try it: <https://tinyurl.com/y3hkka6s>

An approach to avoid recursion

Add `rdf:type` arcs for every resource and use `sh:class`

```
:User a sh:NodeShape ;
  sh:property [
    sh:path    schema:worksFor ;
    sh:class   :Company ;
  ] .
```

```
:Company a sh:Shape ;
  sh:property [
    sh:path    schema:name ;
    sh:datatype xsd:string ;
  ] ;
  sh:property [
    sh:path    schema:employee ;
    sh:class   :User ;
  ] .
```



```
:alice a :User ;
      schema:worksFor :OneCompany .
:bob   a :User ;
      schema:worksFor :OneCompany .
:carol a :User ;
      schema:worksFor :Something .
:OneCompany a :Company ;
          schema:name "One" ;
          schema:employee :alice, :bob, :carol .
```



Try it: <https://tinyurl.com/yynnts8o>

Logical Operators

Constraint	Description
and	Conjunction of a list of shapes
or	Disjunction of a list of shapes
not	Negation of a shape
xone	Exactly one (similar XOR for 2 arguments)

Conjunction: and

Although it can be declared explicitly, it is the default behavior

```
:User a sh:NodeShape ;  
  sh:and (  
    [ sh:property [  
      sh:path      schema:name;  
      sh:minCount 1;  
    ]  
    [ sh:property [  
      sh:path      schema:affiliation;  
      sh:minCount 1;  
    ]  
  ]  
) .
```

≡

```
:User a sh:Shape ;  
  [ sh:property [  
    sh:path      schema:name;  
    sh:minCount 1;  
  ]  
  [ sh:property [  
    sh:path      schema:affiliation;  
    sh:minCount 1;  
  ]  
]  
.
```

Disjunction: or

```
:User a sh:NodeShape ;  
  sh:or (  
    [ sh:property [  
      sh:predicate foaf:name;  
      sh:minCount 1;  
    ]  
    [  
      sh:property [  
        sh:predicate schema:name;  
        sh:minCount 1;  
      ]  
    ]  
  ) .
```

```
:alice schema:name "Alice" .
```

```
:bob foaf:name "Robert" .
```

```
:carol rdfs:label "Carol" .
```



Negation: not

```
:NotFoaf a sh:NodeShape ;  
  sh:not [ a sh:Shape ;  
    sh:property [  
      sh:predicate foaf:name ;  
      sh:minCount 1 ;  
    ] ;  
  ] .
```


```
:alice schema:name "Alice" .  
:bob    foaf:name "Robert" .  
:carol  rdfs:label "Carol" .
```



Exactly one: xone

```
:UserShape a sh:NodeShape ;  
  sh:targetClass :User ;  
  sh:xone (  
    [ sh:property [  
      sh:path      foaf:name;  
      sh:minCount 1;  
    ]  
    [  
      sh:property [  
        sh:path      schema:name;  
        sh:minCount 1;  
      ]  
    ]  
  ) .
```

```
:alice a :User ;           #Passes as :User  
      schema:name "Alice" .  
  
:bob   a :User ;           #Passes as :User  
      foaf:name   "Robert" .  
  
:carol a :User ;           #Fails as :User  
      foaf:name   "Carol";  
      schema:name "Carol" .  
  
:dave  a :User ;           #Fails as :User  
      rdfs:label  "Dave" .
```



Exercise


IF-THEN pattern

All products must have `:productID` and, if a product has `rdf:type schema:Vehicle` then it must have the properties `schema:vehicleEngine` and `schema:fuelType`

```
:p1 a :Book;                # Conforms
    schema:productID        "P1" .

:p2 a schema:Vehicle ;      # Conforms
    schema:productID        "P2" ;
    schema:fuelType         "Gasoline" ;
    schema:vehicleEngine    "X2" .

:p3 a schema:Vehicle ;      # Fails
    schema:productID        "P3" .
```

Exercise

IF-THEN-ELSE pattern

All products must have `:productID` and, if a product has `rdf:type schema:Vehicle` then it must have the properties `schema:vehicleEngine` and `schema:fuelType` else it must have `schema:category` with a string value.

Value ranges

Constraint	Description
minInclusive	$\leq$
maxInclusive	$\geq$
minExclusive	$<$
maxExclusive	$>$

```
:Rating a sh:NodeShape ;  
  sh:property [  
    sh:path          schema:ratingValue ;  
    sh:minInclusive  1 ;  
    sh:maxInclusive  5 ;  
    sh:datatype      xsd:integer  
  ] .
```

```
:bad          schema:ratingValue 1 .  
:average      schema:ratingValue 3 .  
:veryGood     schema:ratingValue 5 .  
:zero         schema:ratingValue 0 . ☹️
```

String based constraints

Constraint	Description
minLength	Restricts the minimum string length on value nodes
maxLength	Restricts the maximum string length on value nodes
pattern	Checks if the string value matches a regular expression

minLength/maxLength

Checks the string representation of the value

This cannot be applied to blank nodes

If minLength = 0, no restriction on string length

```
:User a sh:NodeShape ;  
  sh:property [  
    sh:path      schema:name ;  
    sh:minLength 4 ;  
    sh:maxLength 10 ;  
  ] .
```

```
:alice schema:name "Alice" .  
:bob schema:name "Bob" .  
:carol schema:name :Carol .  
:strange schema:name _:strange .
```



?



pattern

Checks if the values matches a regular expression
It can be combined with sh:flags

```
:Product a sh:NodeShape ;  
  sh:property [  
    sh:path      schema:productID ;  
    sh:pattern    "^P\\d{3,4}" ;  
    sh:flags      "i" ;  
  ] .
```

```
:car      schema:productID "P2345" .  
:bus      schema:productID "p567" .  
:truck    schema:productID "P12" .  
:bike     schema:productID "B123" .
```



Language based constraints

Constraint	Description
languageIn	Declares the allowed languages of a literal
uniqueLang	Specifies that no pair of nodes can have the same language tag

languageIn

Specifies the allowed language that a literal can have

```
:ProductShape a sh:NodeShape;  
  sh:targetClass :Product ;  
  sh:property [  
    sh:path      rdfs:label ;  
    sh:languageIn ("es" "en" "fr")  
  ] .
```

```
:p234 a :Product ;  
  rdfs:label "jamón"@es, "ham"@en .
```

```
:p235 a :Product ;  
  rdfs:label "milk"@en .
```

```
:p236 a :Product ;  
  rdfs:label "Käse"@de .
```



```
:p237 a :Product ;  
  rdfs:label "patatas"@es ,  
            "kartofeln"@de .
```



uniqueLang

Checks that no pair of nodes use the same language tag


```
:CountryShape a sh:NodeShape ;  
  sh:targetClass :Country ;  
  sh:property [  
    sh:path      skos:prefLabel ;  
    sh:uniqueLang true  
  ] .
```

```
:spain  a :Country;  
  skos:prefLabel "Spain"@en,  
                 "España"@es .  
  
:france a :Country;  
  skos:prefLabel "France",  
                 "France"@en,  
                 "Francia"@es .
```

```
:italy  a :Country .
```

```
:usa    a :Country;  
  skos:prefLabel "USA"@en,  
                 "United States"@en.
```





Exercise

Nodes must have exactly one literal per language in English and Spanish for property `skos:prefLabel`

Property pair constraints

Constraint	Description
equals	The sets of values of both properties at a given focus node must be equal
disjoint	The sets of values of both properties at a given focus node must be different
lessThan	The values must be smaller than the values of another property
lessThanOrEquals	The values must be smaller or equal than the values of another property

```
:User a sh:NodeShape ;
sh:property [
  sh:path schema:givenName ;
  sh>equals foaf:firstName
];
sh:property [
  sh:path schema:givenName ;
  sh:disjoint schema:lastName
] .
```

```
:alice schema:givenName "Alice";
       schema:lastName  "Cooper";
       foaf:firstName   "Alice" .

:bob   schema:givenName "Bob";
       schema:lastName  "Smith" ;
       foaf:firstName   "Robert" .

:carol schema:givenName "Carol";
       schema:lastName  "Carol" ;
       foaf:firstName   "Carol" .
```



Closed shapes

Constraint	Description
closed	Valid resources must only have values for properties that appear in <code>sh:property</code>
ignoredProperties	Optional list of properties that are also permitted

```
:User a sh:NodeShape ;  
  sh:closed true ;  
  sh:ignoredProperties ( rdf:type ) ;  
  sh:property [  
    sh:path schema:givenName ;  
  ] ;  
  sh:property [  
    sh:path schema:lastName ;  
  ] .
```

```
:alice schema:givenName "Alice";  
        schema:lastName "Cooper" .  
  
:bob    a :Employee ;  
        schema:givenName "Bob";  
        schema:lastName "Smith" .  
  
:carol  schema:givenName "Carol";  
        schema:lastName "King" ;  
        rdfs:label "Carol" .
```



Qualified value shapes

Problem with repeated properties

Example: Books have two IDs (an isbn and an internal code)

```
:Book a sh:NodeShape ;  
  sh:property [  
    sh:path      schema:productID ;  
    sh:minCount  1;  
    sh:datatype  xsd:string ;  
    sh:pattern    "^isbn"  
  ];  
  sh:property [  
    sh:path      schema:productID ;  
    sh:minCount  1;  
    sh:datatype  xsd:string ;  
    sh:pattern    "^code"  
  ] .
```

```
:b1 schema:productID "isbn:123-456-789" ;  
    schema:productID "code234" .
```

It fails!!

Qualified value shapes

Qualified value shapes verify that certain number of values of a given property have a given shape

```
:Book a sh:NodeShape;  
sh:property [  
  sh:path schema:productID ;  
  sh:minCount 2; sh:maxCount 2; ];  
sh:property [  
  sh:path schema:productID ;  
  sh:qualifiedMinCount 1 ;  
  sh:qualifiedValueShape [  
    sh:pattern "^isbn"  
  ]];  
sh:property [  
  sh:path schema:productID ;  
  sh:qualifiedMinCount 1 ;  
  sh:qualifiedValueShape [  
    sh:pattern "^code"  
  ]]
```

```
:b1 schema:productID "isbn:123-456-789" ;  
    schema:productID "code234" .
```

Non-validating constraints

Can be useful to annotate shapes or design UI forms

Constraint	Description
name	Provide human-readable labels for a property
description	Provide a description of a property
order	Relative order of the property
group	Group several constraints together

```
:User a sh:NodeShape ;
sh:property [
  sh:path schema:url ;
  sh:name "URL";
  sh:description "User URL";
  sh:order 1
];
sh:property [
  sh:path schema:name ;
  sh:name "Name";
  sh:description "User name";
  sh:order 2
] .
```

Non-validating constraints

```
:User a sh:NodeShape ;  
  sh:property [ sh:path schema:url ;  
    sh:name "URL";  
    sh:group :userDetails  
  ] ;  
  sh:property [ sh:path schema:name ;  
    sh:name "Name"; sh:group :userDetails  
  ] ;  
  sh:property [ sh:path schema:address ;  
    sh:name "Address"; sh:group :location  
  ] ;  
  sh:property [ sh:path schema:country ;  
    sh:name "Country"; sh:group :location  
  ] .
```

```
:userDetails a sh:PropertyGroup ;  
  sh:order 0 ;  
  rdfs:label "User details" .  
  
:location a sh:PropertyGroup ;  
  sh:order 1 ;  
  rdfs:label "Location" .
```

An agent could generate a form like:

User details

URL: _____

Name: _____

Location

Address: _____

Country: _____

SHACL-SPARQL

SPARQL constraints

Constraints based on SPARQL code.

When the SPARQL query return validation errors a violation is reported

SPARQL constraints have type sh:SPARQLConstraint

Constraint	Description
message	Message in case of error
sparql	SPARQL code that is run
prefixes	Points to namespace prefix declarations defined by sh:declare: Each one has: sh:prefix: Prefix alias sh:namespace: namespace IRI

SPARQL constraints

Special variables are pre-bound by the SHACL-SPARQL processor

Constraint	Description
<code>\$this</code>	Focus Node
<code>\$shapesGraph</code>	Can be used to query the shapes graph in named graphs Similar to: <code>GRAPH \$shapesGraph { ... }</code>
<code>\$currentShape</code>	Current shape

SPARQL constraints

Mappings between result rows and error validation information

Constraint	Description
sh:focusNode	Value of <code>\$this</code> variable
sh:subject	Value of <code>?subject</code> variable
sh:predicate	Value of <code>?predicate</code> variable
sh:object	Value of <code>?object</code> variable
sh:message	Value of <code>?message</code> variable
sh:sourceConstraint	The constraint that was validated against
sh:sourceShape	The shape that was validated against
sh:severity	sh:ViolationError by default or the value of sh:severity

SPARQL constraints

Example: Name must be the concatenation of singleName and familyName

```
:UserShape a sh:NodeShape ;
sh:targetClass :User ;
sh:sparql [ a sh:SPARQLConstraint ;
  sh:message "schema:name must equal schema:givenName+schema:familyName";
  sh:prefixes [ sh:declare [
    sh:prefix "schema" ;
    sh:namespace "http://schema.org/"^^xsd:anyURI ;
  ] ] ;
sh:select
  """SELECT $this (schema:name AS ?path) (?name as ?value)
  WHERE {
    $this schema:name ?name .
    $this schema:givenName ?givenName .
    $this schema:familyName ?familyName .
    FILTER (!isLiteral(?value) ||
      !isLiteral(?givenName) || !isLiteral(?familyName) ||
      concat(str(?givenName), ' ', str(?familyName))!=?name )
  }""" ;
] .
```

```
:alice a :User ;
  schema:givenName "Alice" ;
  schema:familyName "Cooper" ;
  schema:name "Alice Cooper" .

:bob a :User ;
  schema:givenName "Bob" ;
  schema:familyName "Smith" ;
  schema:name "Robert Smith" .
```



SPARQL constraint components

SHACL-SPARQL allows to declare custom constraint components
Once defined, they can be used like built-in constraint components

```
:ProductShape a sh:NodeShape ;  
  sh:targetClass :Product ;  
  sh:property [  
    sh:path      :color ;  
    :size        3 ;  
    sh:minCount  1 ;  
  ] .
```



```
:c1 :color (255 0 255) .
```

```
:c2 :color (255 0 210 345) . ☹️
```

```
:c3 :color (255 0) . ☹️
```

SPARQL constraint components

```
:FixedListConstraintComponent
a sh:ConstraintComponent ;
sh:parameter [
  sh:path          :size ;
  sh:name           "Size of list" ;
  sh:description    "The size of the list" ;
] ;
sh:labelTemplate "Size of values: \"{$size}\"" ;
sh:propertyValidator :fixedLengthValidator .
```

Two types of validators:
 SPARQLSelectValidator
 SPARQLASKValidator

```
:fixedLengthValidator a sh:SPARQLSelectValidator ;
sh:message
  "{$PATH} must have length {?size}, not {?count}" ;
sh:prefixes [ sh:declare [
  sh:prefix "rdf" ;
  sh:namespace
    "http://www.w3.org/1999/02/22-rdf-syntax-ns#"
] ] ;
sh:select """SELECT $this ?value $count WHERE {
  $this $PATH ?value .
  { SELECT $this ?value
    (COUNT(?member) AS ?count)
    $size WHERE {
      ?value rdf:rest*/rdf:first ?member
    } GROUP BY $this ?value $size
  }
  FILTER (!isBlank(?value) || ?count != $size)
}"""
.
```

SPARQL constraint components

Property	Description
sh:parameter	Declares the parameters of the constraint component The values are subclasses of property shapes sh:path declares the parameter name sh:optional declares if the parameter is optional
sh:labelTemplate	Suggests how constraints are rendered. Can refer to parameter names using: \$varName
sh:nodeValidator	Associates a node shape validator
sh:propertyValidator	Associates a property shape validator


SPARQL based validators can be SELECT or ASK based validators

ShEx and SHACL: Several common features...

	ShEx	SHACL
Both employ the word "shape"	✓	✓
Can be used to validate RDF graphs	✓	✓
Node constraints	✓	✓
Constraints on incoming/outgoing arcs	✓	✓
Cardinalities on properties	✓	✓
RDF syntax	✓	✓
Extension mechanism	✓	✓

ShEx and SHACL compared

More information in chapter 7 of Validating RDF data book



2017 HTML version:


<http://book.validatingrdf.com>

Or in some talks like:

https://labra.weso.es/talk/2018_validatingrdfdata_stanford/

ShEx and SHACL

description - validation - constraints



DCTAP

Metadata model

Tabular: CSV, Spreadsheets

Easy to understand and edit by domain experts

It can be used as a template and a *single-source-of-truth*

DCTAP can be converted to Shapes (ShEx/SHACL/etc.)



DCTAP example

shapeID	propertyID	propertyLabel	mandatory	repeatable	valueDataType	valueShape
Researcher	rdfs:label	Label	TRUE	FALSE	xsd:string	
	:birthPlace	Place of birth	FALSE	FALSE		Place
	:birthDate	Date of birth	FALSE	FALSE	xsd:date	
	:employer	Employer	FALSE	TRUE		Organization
Place						
Organization						

```
<Researcher> {  
  :name      xsd:string      ;  
  :birthPlace @<Place>      ? ;  
  :birthDate  xsd:date       ? ;  
  :employer   @<Organization> * ;  
}
```

In ShEx

Contents

Introduction to Knowledge graphs

Types of Knowledge Graphs:

RDF, Property graphs, Wikibase, RDF-Star

Shaping RDF: ShEx & SHACL, DCTAP

Shaping other types of Knowledge graphs:

Wikibase and Wikidata graphs

Property Graphs

RDF-1.2




Wikibase and RDF

Wikibase graphs are also available through SPARQL endpoint

Internally, Wikibase has 2 DBs:

- Relational database (MariaDB)
- RDF Triplestore (Blazegraph)
- [Plans to update](#)




```
select ?name ?date ?country where {  
  wd:Q80 wdt:P1559 ?name .  
  wd:Q80 wdt:P569 ?date .  
  wd:Q80 wdt:P19 ?place .  
  ?place wdt:P17 ?country  
}
```

?name	?date	?country
Tim Berners-lee	1955-06-08	:UK

Try it: <https://w.wiki/5yGu>

Wikibase and RDF: Entity Schemas

If we have RDF, we can use ShEx to describe and validate entities



Entity Schemas

They can be used to describe Wikidata entities

Adopted in 2019 as a new Wikidata namespace Exxx

Example:

<https://www.wikidata.org/wiki/EntitySchema:E10>

Directory of entity schemas:

https://www.wikidata.org/wiki/Wikidata:Database_reports/EntitySchema_directory

Example of an Entity Schema

Q80.ttl

```
wd:Q80 rdf:type wikibase:Item ;
    wdt:P31 wd:Q5 ;
    wdt:P19 wd:Q84 ;
    wdt:P569 "1955-06-08T00:00:00Z"^^xsd:dateTime ;
    wdt:P108 wd:Q42944 ;
    p:P108 s:Q80-fcba864c, :Q80-4fe7940f
    #...
    .

:Q80-4fe7940f rdf:type wikibase:Statement ;
    wikibase:rank wikibase:NormalRank ;
    ps:P108 wd:Q42944 ;
    pq:P580 "1984-01-01T00:00:00Z"^^xsd:dateTime ;
    pq:P582 "1994-01-01T00:00:00Z"^^xsd:dateTime .

s:Q80-fcba864c a wikibase:Statement ;
    wikibase:rank wikibase:NormalRank ;
    ps:P108 wd:Q42944 ;
    pq:P580 "1980-06-01T00:00:00Z"^^xsd:dateTime ;
    pq:P582 "1980-12-01T00:00:00Z"^^xsd:dateTime .
```

Entity-schema - ShEx

```
PREFIX pq: <.../prop/qualifier/>
PREFIX ps: <.../prop/statement/>
PREFIX p: <.../prop/>
PREFIX wdt: <.../prop/direct/>
PREFIX wd: <.../entity/>
PREFIX xsd: <...XMLSchema#>

<Researcher> {
    wdt:P31 [ wd:Q5 ] ;
    wdt:P19 @<Place> ;
    wdt:P569 xsd:dateTime ;
    wdt:P108 @<Employer> * ;
    p:P108 { ps:P108 @<Employer> ;
              pq:P580 xsd:dateTime ? ;
              pq:P582 xsd:dateTime *
            } *
}
<Place> { }
<Employer> { }
```

Using Entity Schemas for validation

Example: <https://www.wikidata.org/wiki/EntitySchema:E371>

wikidata.org/wiki/EntitySchema:E371

Click here to Apply now
This application is open until Sunday 8th December, 2024

[Help with translations!]

Researcher (test) (E371)

language code	label	description	aliases	edit
en	Researcher (test)	Schema for researcher created as a test for a paper about WShEx	researcher	edit

check entities against this Schema [edit](#)

```

PREFIX wdt: <http://www.wikidata.org/prop/direct/>
PREFIX wd: <http://www.wikidata.org/entity/>
PREFIX pq: <http://www.wikidata.org/prop/qualifier/>
PREFIX ps: <http://www.wikidata.org/prop/statement/>
PREFIX p: <http://www.wikidata.org/prop/>
PREFIX xsd: <http://www.w3.org/2001/XMLSchema#>

# Example SPARQL query (Tim Berners Lee)
# select ?p { values ?p { wd:Q80 }}
# This schema has been created as a simple demo for ShEx and WShEx

start = @<Researcher>

<Researcher> {
  wdt:P31 [ wd:Q5 ] ;
  wdt:P19 @<Place> ;
  wdt:P569 xsd:dateTime ? ;
  wdt:P108 @<Organization> * ;
  p:P108 {
    ps:P108 @<Organization> ;
    pq:P580 xsd:dateTime ? ;
    pq:P582 xsd:dateTime ?
  } * ;
} * ;

```

ShEx2 — Simple Online Validator

```

PREFIX wdt: <http://www.wikidata.org/prop/direct/>
PREFIX wd: <http://www.wikidata.org/entity/>
PREFIX pq: <http://www.wikidata.org/prop/qualifier/>
PREFIX ps: <http://www.wikidata.org/prop/statement/>
PREFIX p: <http://www.wikidata.org/prop/>
PREFIX xsd: <http://www.w3.org/2001/XMLSchema#>

# Example SPARQL query (Tim Berners Lee)
# select ?p { values ?p { wd:Q80 }}
# This schema has been created as a simple demo for ShEx and WShEx

start = @<Researcher>

<Researcher> {
  wdt:P31 [ wd:Q5 ] ;
  wdt:P19 @<Place> ;
  wdt:P569 xsd:dateTime ? ;
  wdt:P108 @<Organization> * ;
  p:P108 {
    ps:P108 @<Organization> ;
    pq:P580 xsd:dateTime ? ;
    pq:P582 xsd:dateTime ?
  } * ;
  wdt:P166 @<Award> * ;
  p:P166 {

```

validate (ctrl-enter)

Query **Entities to check**


@

✓wd:Q80@START

WShEx

Although Entity Schemas and ShEx just work, they are indirectly describing Wikibase

WShEx has been proposed as a language to describe the Wikibase data model?



<https://www.weso.es/WShEx/>

Wikibase RDF representation



Item
Discussion

Tim Berners-Lee (Q80)

employer (P108)

CERN (Q42944)

start time (P580) 1984

end time (P582) 1994

RDF

```

wd:Q80 wdt:P108 wd:Q42944 ;
p:P108 s:Q80-fcba864c
...
s:Q80-fcba864c a wikibase:Statement ;
ps:P108 wd:Q42944 ;
pq:P580 1984 ;
pq:P582 1994 .

```

Could be represented as

```

:Q80 :P108 :Q42944 { |
:P580 1984 ;
:P582 1994
| }

```

Inspired by RDF-1.2 annotated triples syntax

ShEx vs WShEx

Entity-schema - ShEx

```
PREFIX pq: <.../prop/qualifier/>
PREFIX ps: <.../prop/statement/>
PREFIX p: <.../prop/>
PREFIX wdt: <.../prop/direct/>
PREFIX wd: <.../entity/>
PREFIX xsd: <...XMLSchema#>

<Researcher> {
  wdt:P31 [ wd:Q5 ] ;
  wdt:P19 @<Place> ;
  wdt:P569 xsd:dateTime ;
  wdt:P108 @<Employer> * ;
  p:P108 { ps:P108 @<Employer> ;
            pq:P580 xsd:dateTime ? ;
            pq:P582 xsd:dateTime ?
          } *
}
<Place> { }
<Employer> { }
```

WShEx

```
PREFIX : <.../entity/>

<Researcher> {
  :P31 [ :Q5 ] ;
  :P108 @<Employer> { | :P580 Time ? ,
                      :P582 Time ?
                    } *
}
<Award> { :P17 @<Country> }
<Country> { }
```

Contents

Introduction to Knowledge graphs

Types of Knowledge Graphs:

RDF, Property graphs, Wikibase, RDF-Star

Shaping RDF: ShEx & SHACL, DCTAP

Shaping other types of Knowledge graphs:

Shaping Wikibase and Wikidata graphs

Shaping Property Graphs

Shaping RDF-1.2




Property graphs

Graph structure with nodes and relationships
(edges)

Nodes and edges can have:

- Labels
- A set of property-value pairs

Edges can be directed/undirected



Shaping Property graphs with GQL

GQL defines the concept of Graph Types

It describes the graph in terms of restrictions on labels, properties, nodes, edges and topology

Graph types constrain the set of nodes that can be contained in a graph

Multiple graphs can refer to the same graph type

Graph types can be created independently:


```
CREATE GRAPH TYPE name { graph type spec }
```

Or when creating the graph:

```
CREATE GRAPH ...content... TYPED { graph type spec }
```


Shaping property graphs with GQL: Example

```
CREATE GRAPH TYPE example {
  (researcher :Human => { name String, birthDate Date } )
  (place :City & :Metropolis => { name String })
  (country :Country => { name String })
  (org :Organization => { name String })
  (researcher) -[ :birthPlace ]-> (place),
  (place) -[ :country ]-> (country),
  (researcher) -[:employer => { start Date, end Date}] -> (org),
}
```



No Cardinality constraints about the topology of the graph

Example:

- How can we indicate that a researcher can work for zero or more employers?

PShEx

Proposal to extend ShEx to handle property graphs

Similar to WShEx, but adapted for Property graphs

We add a new description level for property-value pairs (in nodes and edges)

It allows to declare cardinality constraints on the topology of the graph



[Extending Shape Expressions for different types of knowledge graphs](http://labra.weso.es/publication/2024_shex_extensions/) , Jose Emilio Labra Gayo, In 1st Workshop on Data Quality meets Machine Learning and Knowledge Graphs, DQMLKG, part of Extended Semantic Web Conference 2024, ESWC24. - 2024, http://labra.weso.es/publication/2024_shex_extensions/

Shaping property graphs: PShEx

PShEx = ShEx extension that allows to describe property graphs

```

<Researcher> [( Human )] [|
  name: String ;
  birthDate: Date ?
|] AND {
  birthPlace: @<Place> ? ;
  employer: @<Org> { | start: Date; end: Date | } *
}
<Place> [( City)]{
  country: @<Country>
}
<Country> {
  name: String
}
<Org> {
  name: String
}
  
```



PGSchema PC

Recent proposal: PGSchema with property constraints

Accepted at K-Cap conference 2025 (<https://www.k-cap.org/>)

More information: <https://www.weso.es/pgschemapc>

The functionality will be integrated in rudof

Contents

Introduction to Knowledge graphs

Types of Knowledge Graphs:

RDF, Property graphs, Wikibase, RDF-Star

Shaping RDF: ShEx & SHACL, DCTAP

Shaping other types of Knowledge graphs:

Shaping Wikibase and Wikidata graphs

Shaping Property Graphs


Shaping RDF 1.2



RDF 1.2

Current working draft: <https://www.w3.org/TR/rdf12-concepts/>

Main novelty: Add statements about triples: reifiers




ShEx for RDF 1.2 (ShEx Star)

Note: work in progress in the roadmap for rudof

```
<Researcher> {
  :name    xsd:string ;
  :employer @<Org> { |
    :start xsd:date,
    :start xsd:date
  } *
}
<Org> {}
```

```
:timbl :name  "Tim Berners Lee";
       :employer :CERN { |
         :start 1980;
         :end   1980
       } { |
         :start 1984;
         :end   1994
       } .
```




SHACL 1.2

Currently under development at W3C: <https://www.w3.org/TR/shacl12-core/>

```
:UserShape a sh:NodeShape ;
  sh:targetClass :User ;
  sh:property [
    sh:path :employer ;
    sh:reificationRequired true ;
    sh:reifierShape [
      sh:property [
        sh:path :start ;
        sh:datatype xsd:integer ;
        sh:minCount 1 ; sh:maxCount 1
      ] ;
      sh:property [
        sh:path :end ;
        sh:datatype xsd:integer ;
        sh:minCount 1 ; sh:maxCount 1
      ]
    ]
  ] .
```

```
:timbl :name "Tim Berners Lee";
      :employer :CERN { |
        :start 1980;
        :end 1980
      } { |
        :start 1984;
        :end 1994
      } .
```

New
The example is already supported in rudo



Convergence on graph schema languages

More theoretical work is currently under development:

Common Foundations for SHACL, ShEx, and PG-Schema, Shqiponja Ahmetaj, Iovka Boneva, Jan Hidders, Katja Hose, Jose Emilio Labra Gayo, Wim Martens, Fabio Mogavero, Filip Murlak, Cem Okulmus, Axel Polleres, Ognjen Savković, Mantas Šimkus, Dominik Tomaszuk, International World Wide Web Conference, Sydney, Australia, 2025 – 2025

https://labra.weso.es/publication/2025_common_foundations_shacl_shex_pgschema/

Conclusions

Several types of Knowledge Graphs

Different models

Could they converge in the future?

Shapes increase the quality of Knowledge graphs

Can be extended for other types of Knowledge Graphs

Wikibase graphs: ShEx, WShEx

Property graphs: PShEx, PGSchema, PGSchemaPC, ...

RDF 1.2: ShEx (next), SHACL 1.2

Could the shapes languages converge in the future?

